

HELİSEL DİFÜZÖRLER / SWIRL DIFFUSERS



ESDA-3

Egevent ESDA-3 serisi helisel üflemeli tavan difüzörleri 2,6 ila 4 metre arasındaki tavan yükseklikleri için ideal hava üfleme terminal üniteleridir. Helezonik devinimle üflenilen hava çok kısa mesafeler içinde oda havasıyla homojen bir karışım sağlar.

ESDA-3 serisi helisel difüzörler kare plakalı dairesel plakalı olmak üzere iki ana tiptedirler. Her tip modelin efektif alanı değişiktir. Her slotta bulunan mistakilen ayarlanabilir damperler vasıtıyla hava üfleme yönünü istediğiniz gibi yönlendirmek mümkündür.



ESDA-3'leri plenum hücreli olarak ta sipariş etmek mümkündür.

Egevent ESDA-3 swirl diffusors are ideal supply units for premises with ceiling heights ranging from 2.6 meters to 4 meters. The air blown to the room follows a spiral "swirl" path which enables thorough mixing with the room air in very short distances.


The ESDA-3 series swirl diffusers are composed of two major versions, namely with square face plate and with circular face plate. Each type has a different effective area. Each slot is equipped with an individually adjustable damper to guide the air throw.

They may be supplied plain or coupled with plenum boxes.


DİFÜZÖR ÖLÇÜLERİ / DIFFUSER DIMENSIONS



ÜFLEME TARZLARI / THROW VARIATIONS



PLENUM HÜCRELER / PLENUM BOXES




Ölçü / Size	C3	A	H1	h1	H2	Ød
300/8 K	298	290	290	170	200	158
400/16 K	398	390	330	190	300	198
500/16 K	498					
600/16 K	598					
625/16 K	623					
500/24 K	498	490	330	190	300	198
600/24 K	598	590	380	215	300	248
625/24 K	623					
600/48 K	598					
625/54 K	623	610	380	215	300	248
800/72 K	798	790	450	250	300	313
825/72 K	823					


- 1- Plenum kutusu
Plenum box
- 2- Giriş yakası
Inlet Spigot
- 3- Dağıtma plakası
Dispersing plate
- 4- Kapama/eglaj damperi
Shut-off/regulating damper
- 5- Çapraz
Traverse
- 6- Dairesel ön plaka için adaptör
Adapter for circular front plate
- 7- Difüzör / Diffuser

Ölçü / Size	ØD3	ØD	I A	H1	h1	H2	Ød
300/8 R	300	290	310	290	170	200	158
400/16 R	400	370	390	330	190	300	198
500/16 R	500						
600/16 R	600						
625/16 R	625						
500/24 R	500	488	510	330	190	300	198
600/24 R	600	560	590	380	215	300	248
625/24 R	625						
600/48 R	600	590	635	380	215	300	248
625/54 R	625	610	635	380	215	300	248
800/72 R	800	790	815	450	250	300	313
825/72 R	825						


SEÇİM TABLOSU-1 / SELECTION DIAGRAM-1



SEÇİM TABLOSU-2 / SELECTION DIAGRAM-2



SES SEVİYELERİ / SOUND POWER LEVELS



SİPARİŞ NOTASYONU

HOW TO ORDER

